

HOT AIR BALLOON CRYSTAL PENDANT - ASSEMBLY INSTRUCTIONS

Thank you for selecting RH Baby & Child lighting. Our assortment is crafted with the highest quality materials that coordinate perfectly with our Baby & Child bedding collections, making it easy to create an elegant nursery or child's bedroom. Each item's surface is sealed, which eliminates the need for polishing and ensures a lasting finish for years to come.

PARTS ENCLOSED:

- (A) Plastic wire connectors (3)
- (B) Mounting plate (1)
- (C) Mounting screws (2)
- (D) Green ground screw (1)
- (E) Canopy screws (2)
- (F) Canopy (1)
- (G) Top ring (1)
- (H) Chain (1)
- (I) 2nd ring (1)
- (J) Sockets (3)
- (K) LED bulbs (3)
- (L) Removable door (1)
- (M) Removable basket (1)

IMPORTANT SAFETY INSTRUCTIONS:

WE RECOMMEND INSTALLATION BY A LICENSED ELECTRICIAN.


This fixture has been rated for up to (3) 4w max Type B LED bulbs (MODEL NO.: C32-4, included) or (3) 40w max Type B incandescent bulbs (not included). To avoid the risk of fire, do not exceed the recommended wattage.

WARNINGS:

All wires are connected. When unpacking, be careful not to pull wires as a bad connection may result. Do not connect electricity until the fixture is fully assembled. To reduce the risk of fire, electrical shock, or personal injury, always turn off and unplug fixture and allow it to cool prior to replacing the lightbulbs. Do not touch bulbs when fixture is turned on or look directly at lit bulbs. Keep flammable materials away from lit bulbs.

THIS PRODUCT IS NOT A TOY AND HAS NO PLAY VALUE.

Direct-Wire Installation



ASSEMBLY & INSTALLATION:

1. Carefully remove all parts from the box and remove all plastic coverings.
2. Turn OFF power to the junction box where the fixture will be installed.
3. Connect the hot wire to the hot junction box wire (usually black or smooth) with a plastic wire connector (A) and wrap the connection with electrical tape. Connect the neutral wire to the neutral junction box wire (usually white or ribbed) with a plastic wire connector (A) and wrap the connection with electrical tape.
4. Attach the ground wire from the fixture to the ground junction box wire from the outlet box (usually green or bare wire). Or wrap the ground wire around the green ground screw (D).
5. Attach mounting plate (B) to the outlet box using the mounting screws (C) and tighten.
6. Attach the canopy (F) to the mounting plate (B) using the canopy screws (E) to secure.
7. Pull out the removable door (L), then insert the LED bulbs (K) into the sockets (J) and screw tightly.
8. Put the removable door back on the fixture and make sure it is well fixed.
9. Hang the removable basket (M) onto the lamp base.
10. Hang one end of the chain (H) onto the top ring (G), then attach the lamp base to the other end of the chain through the 2nd ring (I), and make sure that both ends of the chain are screwed on well.
11. Restore power to the junction box and test fixture.
12. Installation is complete.

CARE INSTRUCTIONS:

Do not use polishes or cleaners, as they will damage the finish. Wipe clean with a soft, dry cloth.