

baby&child

RESTORATION HARDWARE

Thank you for selecting Restoration Hardware Baby & Child lighting. Our assortment is crafted with the highest quality materials that coordinate perfectly with our Baby & Child bedding collections, making it easy to create an elegant nursery or child's bedroom. The item's surface is sealed, which eliminates the need for polishing and ensures a lasting finish for years to come.

PARTS ENCLOSED:

- (A) Mounting Plate (1)
- (B) Plastic Wire Connector (2)
- (C) Ground Screw (1)
- (D) Mounting Screw (2)
- (E) Screw (2)
- (F) Canopy (1)
- (G) Socket
- (H) Bulb (1) (Included)
- (I) Screw with Nut (3)
- (J) Pendant

IMPORTANT SAFETY INSTRUCTIONS:

WE RECOMMEND INSTALLATION BY A LICENSED ELECTRICIAN. This fixture has been rated for up to 1 (one) 100-watt maximum A bulb. To avoid the risk of fire, do not exceed the recommended wattage.

WARNINGS:

All wires are connected. When unpacking, be careful not to pull wires as a bad connection may result. Do not connect electricity until your fixture is fully assembled. To reduce the risk of fire, electrical shock, or personal injury, always turn off fixture and allow it to cool prior to replacing the light bulbs. Do not touch bulb when fixture is turned on or look directly at lit bulbs. Keep flammable materials away from lit bulb.

THIS IS NOT A TOY AND THE PRODUCT HAS NO PLAY VALUE

VINTAGE CROWN FLUSHMOUNT

Direct Wire Installation

TO ASSEMBLE:

1. Carefully remove all parts from the box and remove all plastic covering.
2. Turn OFF power to the junction box where the flush mount will be installed.
3. Connect the hot wire (the black wire is hot wire) to the hot junction box wire with a plastic wire connector (B) and wrap the connection with electrical tape. Connect the neutral wire (the white wire is neutral wire) to the neutral junction box wire with a plastic wire connector (B) and wrap the connection with electrical tape.
4. Attach the ground wire (the silver wire is the ground wire) from the fixture to the ground junction box wire in the outlet the box, or wrap the ground wire around the green ground screw (C).
5. Attach the mounting plate (A) to the outlet box using the mounting screws (D) and tighten.
6. Attach the canopy (F) to the mounting plate (A) using the mounting screws (E).
7. Insert (1) 100-watt bulb (L).
8. Attach the flushmount to the canopy (F) using the screw with the nut (I).
9. Restore power to the junction box and test fixture.
10. Installation is complete.

CARE INSTRUCTIONS:

Do not use polishes or cleaners on your lamp.
JUST WIPE CLEAN WITH A SOFT CLOTH.

