



MANOR COURT CRYSTAL 3-ARM SCONCE - ASSEMBLY INSTRUCTIONS

Thank you for selecting RH Baby & Child lighting. Our assortment is crafted with the highest quality materials that coordinate perfectly with our Baby & Child bedding collections, making it easy to create an elegant nursery or child's bedroom. Each item's surface is sealed, which eliminates the need for polishing and ensures a lasting finish for years to come.

PARTS ENCLOSED:

- (A) Wire Connectors (3)
- (B) Mounting Plate (1)
- (C) Mounting Plate Screws (2)
- (D) Back Plate (1)
- (E) Plate Screws (2)
- (F) Drywall Anchor (1)
- (G) Screw (1)
- (H) LED Bulbs (3)
- (I) Socket Sleeves (3)
- (J) Sockets (3)
- (K) Green Ground Wire Screw (1)

IMPORTANT SAFETY INSTRUCTIONS:

Professional installation is strongly recommended. These instructions are provided for your safety. It is important that they are read carefully and completely before installation of the fixture.

This fixture has been rated for up to (3) 2w max Type B LED bulbs (MODEL NO.: C32-2, included) or (3) 40w max Type B incandescent bulbs (not included). To avoid the risk of fire, do not exceed the recommended wattage.

WARNINGS:

All wires are connected. When unpacking, be careful not to pull wires, as a bad connection may result. Do not connect electricity until the fixture is fully assembled. To reduce the risk of fire, electrical shock or personal injury, always turn off and unplug fixture and allow it to cool prior to replacing lightbulbs. Do not touch bulbs when fixture is turned on or look directly at lit bulbs. Keep flammable materials away from lit bulbs.

Dry UL listed: suitable for use indoors in dry locations not directly exposed to excessive moisture and water.

THIS PRODUCT IS NOT A TOY AND HAS NO PLAY VALUE.

ASSEMBLY & INSTALLATION:

1. Carefully remove all parts from the box and remove all plastic coverings.
2. SHUT OFF THE MAIN ELECTRICAL SUPPLY FROM THE MAIN FUSE BOX / CIRCUIT BREAKER.
3. Attach the sconce to the wall and drill a hole in the wall for the drywall anchor (F).
4. Guide the wiring from the outlet box through center hole in the mounting plate (B).
5. Attach the mounting plate (B) to the outlet box using the mounting plate screws (C) to secure.
6. Attach the ground wire (usually green or bare wire) from the fixture to the ground junction box wire from the outlet box (usually green or bare wire). Or wrap the ground wire around the green ground wire screw (K).
7. Connect the hot wire to the hot junction box wire (usually black) with a wire connector (A) and wrap the connection with electrical tape. Connect the neutral wire to the neutral junction box wire (usually white) with a plastic wire connector (A) and wrap the connection with electrical tape.
8. Attach the back plate (D) to the mounting plate (B) and use the plate screw (E) to secure the back plate.
9. Attach the screw (G) to the drywall anchor (F) and tighten to secure the
10. Place the socket sleeves (I) onto the sockets (J).
11. Insert (3) LED bulbs (H) into the threaded sockets (J).
12. Restore power to the junction box and test fixture.
13. Installation is complete.

CARE INSTRUCTIONS:

Do not use polishes or cleaners, as they will damage the finish. Wipe clean with a soft, dry cloth.

