

baby&child

RESTORATION HARDWARE


Thank you for selecting Restoration Hardware Baby & Child lighting. Our assortment is crafted with the highest quality materials that coordinate perfectly with our Baby & Child bedding collections, making it easy to create an elegant nursery or child's bedroom. The item's surface is sealed, which eliminates the need for polishing and ensures a lasting finish for years to come.

PARTS ENCLOSED:

- A [1] Mounting Plate
- B [2] Plastic Wire Connector
- C [1] Ground Screw
- D [2] Mounting Screw
- E [1] Canopy
- F [1] Ring
- G Chandelier
- H [6] Sleeve
- I [6] Bulb [Included]

EMILE CHANDELIER

Direct Wire Installation



IMPORTANT SAFETY INSTRUCTIONS:

THIS FIXTURE MUST BE INSTALLED BY A LICENSED ELECTRICIAN. This fixture has been rated for up to 6 (six) 40-watt maximum TYPE E12 candelabra bulbs. To avoid the risk of fire, do not exceed the recommended wattage.

WARNINGS:

All wires are connected. When unpacking, be careful not to pull wires as a bad connection may result. Do not connect electricity until your fixture is fully assembled. To reduce the risk of fire, electrical shock, or personal injury, always turn off fixture and allow it to cool prior to replacing the light bulbs. Do not touch bulb when fixture is turned on or look directly at lit bulbs. Keep flammable materials away from lit bulb.

THIS IS NOT A TOY AND THE PRODUCT HAS NO PLAY VALUE

TO ASSEMBLE:

1. Carefully remove all parts from the box and remove all plastic covering.
2. Turn OFF power to the junction box where the chandelier will be installed.
3. Connect the live wire (labeled with an "L") to the live junction box wire with a plastic wire connector (B) and wrap the connection with electrical tape.
4. Connect the neutral wire (labeled with an "N") to the neutral junction box wire with a plastic wire connector (B) and wrap the connection with electrical tape.
5. Attach the ground wire from the fixture to the ground junction box wire from the outlet the box or wrap the ground wire (not labeled) around the green ground screw (C).
6. Attach Mounting plate (A) to the outlet box using the Mounting screws (D) and tighten.
7. Attach the Canopy (E) to the Mounting plate (A) using the Ring (F) and tighten.
8. Put the sleeves (H) on the sockets and insert (6) 60-watt bulbs (I) included.
9. Restore power to the junction box and test fixture.
10. Installation is complete.

CARE INSTRUCTIONS:

Do not use polishes or cleaners on your lamp. Just wipe clean with a soft cloth.