

ORION PENDANT - ASSEMBLY INSTRUCTIONS

Thank you for selecting RH Baby & Child lighting. Our assortment is crafted with the highest quality materials that coordinate perfectly with our Baby & Child bedding collections, making it easy to create an elegant nursery or child's bedroom. Each item's surface is sealed, which eliminates the need for polishing and ensures a lasting finish for years to come.

PARTS ENCLOSED:

- (A) Ceiling anchor (4)
- (B) Ceiling plate (1)
- (C) Ceiling screw (4)
- (D) Connector screw (2)
- (E) Steel wire connector (1)
- (F) Plastic wire connector (3)
- (G) Steel wire (1)
- (H) Green ground screw (1)
- (I) Mounting plate (1)
- (J) Mounting screw (2)
- (K) Canopy screw (2)
- (L) Canopy (1)
- (M) Allen key (1)
- (N) M4 screw (4)
- (O) Extension rod (1, 18" long)
- (P) Extension rod (2, 12" long)
- (Q) Extension rod (1, 6" long)
- (R) Wire housing (1)
- (S) LED bulb (12) (included)
- (T) Lamp body (1)

IMPORTANT SAFETY INSTRUCTIONS:

WE RECOMMEND INSTALLATION BY A LICENSED ELECTRICIAN.

This fixture has been rated for up to (12) 2w max Type T LED bulbs (included) or (12) 25w max Type T incandescent bulbs (not included). To avoid the risk of fire, do not exceed the recommended wattage.

WARNINGS:

All wires are connected. When unpacking, be careful not to pull wires, as a bad connection may result. Do not connect electricity until the fixture is fully assembled. To reduce the risk of fire, electrical shock, or personal injury, always turn off the fixture and allow it to cool prior to replacing the lightbulb. Do not touch bulb when fixture is turned on or look directly at lit bulb. Keep flammable materials away from lit bulb.

THIS PRODUCT IS NOT A TOY AND HAS NO PLAY VALUE.

WARNING: This lighting fixture contains lead, a chemical known to the State of California to cause cancer, birth defects and/or other reproductive harm. Wash hands after installing, handling, cleaning or otherwise touching this light fixture.

ASSEMBLY INSTRUCTIONS:

1. Carefully remove all parts from the box and remove plastic covering.
2. Turn OFF power to the junction box where the fixture will be installed.
3. Insert (12) 2W max Type T LED bulbs (S) into the sockets.
4. Drill 4 holes in the ceiling that align with the holes on the ceiling plate (B) and insert ceiling anchors (A). Screw 4 ceiling screws (C) into anchors.
5. Pull the steel wire (G) through one hole of the steel wire connector (E) and then to the side hole of the ceiling plate (B). Then cross to the other hole of the connector (E) and use 2 connector screws (D) to secure tightly based on your desired hanging height.
6. Connect the hot wire to the hot junction box wire (usually black or smooth) with a plastic wire connector (F) and wrap the connection with electrical tape. Connect the neutral wire to the neutral junction box wire (usually white or ribbed) with a plastic wire connector (F) and wrap the connection with electrical tape.
7. Attach the ground wire from the fixture to the ground junction box wire from the outlet box (usually green or bare wire). Or wrap the ground wire around the green ground screw (H).
8. Attach mounting plate (I) to the outlet box using the mounting screws (J) and tighten.
9. Attach the canopy (L) to the mounting plate (I) using the canopy screws (K) to secure.
10. Screw the extension rod (O) onto the thread of canopy (L), connect the extension rod (P) to (O), (P) to (P), (Q) to (P), then screw extension rod (Q) onto the thread of wire housing (R). Screw the end of each rod by using Allen key (M) and M4 screws (N) to make sure all rods are properly fixed.
11. Restore power to the junction box and test fixture.
12. Installation is complete.

CARE INSTRUCTIONS:

Wipe clean with soft, dry cloth.
Do not use polishes or cleaners, as they will damage the finish.

Direct-Wire Installation

