

# baby&child

RESTORATION HARDWARE

Thank you for selecting Restoration Hardware Baby & Child lighting. Our assortment is crafted with the highest quality materials that coordinate perfectly with our Baby & Child bedding collections, making it easy to create an elegant nursery or child's bedroom. The item's surface is sealed, which eliminates the need for polishing and ensures a lasting finish for years to come.

#### PARTS ENCLOSED:

- (A) Mounting plate (1)
- (B) Canopy (1)
- (C) Screw caps (2)
- (D) Top tier crystals (27)
- (E) Middle tier crystals (24)
- (F) Bottom tier crystals (17)

#### HARDWARE INCLUDED:

- (a) Green ground screw (1)
- (b) Plastic wire connector (3)
- (c) Mounting screw (2)
- (d) Screw on mounting plate (2)
- (e) Bulb (1) (not included)

#### IMPORTANT SAFETY INSTRUCTIONS:

This fixture must be installed by a licensed electrician.

This fixture has been rated for up to (1) 60-watt maximum TYPE A standard incandescent light bulb (not included).

To avoid the risk of fire, do not exceed the recommended wattage.

#### WARNINGS:

All wires are connected. When unpacking, be careful not to pull wires as a bad connection may result. Do not connect electricity until your pendant is fully assembled.

To reduce the risk of fire, electrical shock, or personal injury, always turn off pendant and allow it to cool prior to replacing light bulb.

Do not touch bulb when fixture is turned on or look directly at lit bulb.

Keep flammable materials away from lit bulb.

## SOHO CRYSTAL FLUSHMOUNT

### Direct Wire Installation

THIS IS NOT A TOY AND THE PRODUCT HAS NO PLAY VALUE

#### TO ASSEMBLE:

1. Carefully remove all parts from the box and remove all plastic covering.
2. Turn OFF power to the junction box where the lamp will be installed.
3. Connect the hot wire on the fixture (labeled with an "L") to the hot junction box wire (usually black or smooth) with a plastic wire connector (b) and wrap the connection with electrical tape. Connect the neutral wire on the light fixture (labeled with an "N") to the neutral junction box wire (usually white or ribbed) with a plastic wire connector (b) and wrap the connection with electrical tape.
4. Attach the ground wire from the fixture to the ground junction box wire from the outlet box (usually green or bare wire), Or wrap the green ground wire around the green ground screw (a).
5. Attach mounting plate (A) to the outlet box using the mounting screws (c) and tighten.
6. Attach the canopy (B) to the mounting plate (A). The threads of the two screws on mounting plate (d) will come through the holes of canopy (B). Use the screw caps (C) to tighten the canopy (B).
7. Crystal strands for different tiers are packed separately inside product package. Hang crystals of top tier (D), middle tier (E) and bottom tier (F) on the fixture.
8. Insert (1) 60-watt Type A incandescent bulb (e) (not included) into the socket.
9. Restore power to the junction box and test lamp fixture.
10. Installation is complete.

#### CARE INSTRUCTIONS:

Do not use polishes or cleaners on your fixture.

JUST WIPE CLEAN WITH SOFT CLOTH.

